

606 L1L/01

|   | Type  | L # | Hits   | Search Text   | DBs              | Time Stamp        | Comments | Error Definition | Errors |
|---|-------|-----|--------|---|------------------|-------------------|----------|------------------|--------|
| 1 | ISS&R | L1  | 10837  | ((385/88,89,92-94) or (257/99,433,712,729,730) or (361/702-704,707,709,711) or (174/52.5)).CCLS.  | US- PGPUB; USPAT | 2005/0 9/12 11:36 |          |                  |        |
| 2 | BRS   | L2  | 761    | stem with (((laser or photo) adj (diode or diodes)) or photodiode or photodiodes or photodetector or photodetectors or (light adj2 (emitter or emitting or receiver or receiving))                                  | US- PGPUB; USPAT | 2005/0 9/12 11:36 |          |                  |        |
| 3 | BRS   | L3  | 253849 | heat near3 (dissipat\$ or sink or sinks or transfer\$ or transports or conducted)   | US- PGPUB; USPAT | 2005/0 9/12 11:36 |          |                  |        |
| 4 | BRS   | L4  | 304    | L2 and (L1 or L3)   | US- PGPUB; USPAT | 2005/0 9/12 11:36 |          |                  |        |
| 5 | BRS   | L5  | 23     | 2 with (pcb or ((circuit or wiring) adj board))   | US- PGPUB; USPAT | 2005/0 9/12 11:37 |          |                  |        |
| 6 | BRS   | L7  | 103    | (to-can or (transistor adj outline) with (((laser or photo) adj (diode or diodes)) or photodiode or photodiodes or photodetector or photodetectors or (light adj2 (emitter or emitting or receiver or receiving)) ) | US- PGPUB; USPAT | 2005/0 9/12 11:38 |          |                  |        |
| 7 | BRS   | L8  | 6      | L7 with (pcb or ((circuit or wiring) adj board))  | US- PGPUB; USPAT | 2005/0 9/12 11:37 |          |                  |        |
| 8 | BRS   | L9  | 4016   | (stem or base) near5 heat near5 (sink or fin)   | US- PGPUB; USPAT | 2005/0 9/12 11:37 |          |                  |        |

| Type | L # | Hits       | Search Text  | DBs                  | Time Stamp              | Comments | Error Definition | Errors |
|------|-----|------------|--|----------------------|-------------------------|----------|------------------|--------|
| 9    | BRS | L10 87     | (2 or 7) and 9   | US - PGPUB;<br>USPAT | 2005/0<br>9/12<br>11:38 |          |                  |        |
| 10   | BRS | L11 509    | header with (((laser or photo) adj (diode or diodes) ) or photodiode or photodiodes or photodetector or photodetectors or (light adj2 (emitter or emitting or receiver or receiving) )                           | US - PGPUB;<br>USPAT | 2005/0<br>9/12<br>11:38 |          |                  |        |
| 11   | BRS | L12 82     | 11 and (3 or 9)  | US - PGPUB;<br>USPAT | 2005/0<br>9/12<br>11:39 |          |                  |        |
| 12   | BRS | L13 1899   | (stem or header or (to-can or (transistor adj outline)) with (pcb or (circuit or wiring) adj board))   | US - PGPUB;<br>USPAT | 2005/0<br>9/12<br>11:39 |          |                  |        |
| 13   | BRS | L14 206299 | (( (laser or photo) adj (diode or diodes) ) or photodiode or photodiodes or photodetector or photodetectors or (light adj2 (emitter or emitting or receiver or receiving) ) or optical or optoelectronic).ti,ab. | US - PGPUB;<br>USPAT | 2005/0<br>9/12<br>11:39 |          |                  |        |
| 14   | BRS | L15 147    | L13 and L14  | US - PGPUB;<br>USPAT | 2005/0<br>9/12<br>11:39 |          |                  |        |
| 15   | BRS | L16 499    | 4 or 5 or 8 or 10 or 12 or 15  | US - PGPUB;<br>USPAT | 2005/0<br>9/12<br>11:40 |          |                  |        |